Safety Data Sheet

1. Identification of the preparation and the Company

1.1 Identification of the preparation

Product name

SINCEM COMP A

1.2 Identification of the Company

Name Full address District and Country Sinit S.r.l. Via V.Chiarugi,76/t 45100 ROVIGO Italy tel. ++39 0425 361961 fax ++39 0425 410115 sinit@tin.it

For urgent inquiries refer to

2. Composition/Information on ingredients

 Name

 EPOXY RESINS (average molecular weight <=700)</td>

 N° Cas
 25068-38-6

 N° CE
 500-033-5

 N° Index 603-074-00-8

Concentr.(C) 100,00 %
 Classification

 Xi
 R36/38

 Xi
 R43

 N
 R51/53

The complete text of -R- phrases is specified in section 16.

3. Danger Identification

3.1 Substance/Preparation Classification

This preparation is dangerous under 67/548/EEC and 1999/45/EC regulations and subsequent amendments. This preparate requires a safety data sheet according to the 91/155/EC regulation and subsequent amendments. Further information on health and/or environmental hazards can be found in sections 11 and 12 of this sheet.

Danger Symbols: Xi-N

Phrases R: 36/38-43-51/53

3.2 Danger Identification

IRRITATING TO EYES AND SKIN. MAY CAUSE SENSITIZATION BY SKIN CONTACT. TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.

4. First-aid measures

EYES: Irrigate copiously with clean, fresh water for at least 15 minutes. Seek medical advice.

SKIN: Wash immediately with plenty of water. Remove contaminated clothing. If irritation persists seek medical attention. Wash contaminated clothing before using them.

INHALATION: Remove to fresh air. If breathing is irregular seek medical advice.

INGESTION: Obtain immediate medical attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person.

5. Fire-fighting measures

Closed containers exposed to heat may lead to pressure rise and explode. For information regarding environmental risks, refer to section 12 of this sheet.

Extinguishing measures: carbon anhydride, foam, water if not otherwise specified on the containers.

Individual protective equipment: equipment complete with helmet and face shield and protection of the neck, insulative jacket and trousers, with bands around the arms, legs and waist and selfbreathing apparatus.

6. Accidental release measures

Extinguish the sources of ignition or heat; cover the spillage with inert absorbent material. Collect as far as possible the resulting mass and discard the remainder by spraying water, if not contraindicated.

For information on environmental and health risks, protection of the respiratory airways, ventilation and individual protective measures refer to the other sections of this sheet.

7. Handling and storage

Make sure that equipment is available for cooling the vessels, to prevent the danger of overpressure and overheating in the event of fire in the vicinity. Refer to the other sections of this data sheet for information relating to health and environmental risks.

8. Exposure controls/personal protection.

In order to minimize exposure as far as possible, it is strongly recommended to use adequate individual protective measures such as: masks suitable for the product, goggles, gloves and overalls. Do not eat, drink or smoke while handling it. Accurately wash the hands with soap and water before meals and at the end of the work shift.

9. Physical and chemical properties

Viscosity Vapour density Solubility Evaporation speed		N.A. N.A. N.A.
Comburent properties Partition coefficient: n-octanol/water pH		N.A. N.A. N.A.
Boiling point Flash point Explosive properties	>	N.A. 61°C N.A. N.A.
Vapour pressure Specific gravity		N.A. N.A.

10. Stability and reactivity

The product is stable in normal conditions of use and storage. Due to thermal decomposition or in the event of a fire vapours may be produced potentially dangerous to health.

11. Toxicological information

Acute effects: stinging eyes. Symptoms may include rubescence, edema, pain and lachrymation. Contact with skin may cause irritation, erythema, edema, dryness and chapped skin. Vapour inhalation may slightly irritate the upper respiratory trait. Ingestion may cause health disorders, including stomach pain and sting, nausea and sickness.

Upon contact with skin, this product causes sensitization (dermatitis). Dermatitis derives from skin irritation on the areas which repeatedly come into contact with the sensitizing agent. Cutaneous lesions may include erythemas, edemas, papules, vescicles, pustules, scurves, ulcerations and exudative phenomena, whose intensity varies according to illness seriousness and affected areas. Scurfy skin, dryness, ulcerations and skin thickening prevail during the acute phase.

12. Ecological information

TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT. RESINE EPOSSIDICHE Evitare la penetrazione nel sottosuolo. Non scaricare il prodotto nelle fogne. Non contaminare acqua in superficie.

13. Disposal considerations

Consider the possibility of burning the product in a suitable inceneritor. Acid or basic products must always be neutralized before undergoing any treatment, including biological treatment whenever feasible. If the waste is solid, it can be disposed of in a landfill.

14. Transport informations

These goods must be transported by vehicles authorized to the carriage of dangerous goods according to the provisions set out in the current edition of the Code of International Carriage of Dangerous Goods by Road (ADR) and in all the applicable national regulations. These goods must be packed in their original packings or in packings made of materials resistant to their content and not reacting dangerously with it. People loading and unloading dangerous goods must be trained on all the risks deriving from these substances and on all actions that must be taken in case of emergency situations.

Road and rail transport:

ADR: Label: Proper Shipping Name:	9,III 9 Materia	UN:3082 pericolosa per l'ambiente, liquida, n.a.s.	
Carriage by sea (shipping):			
IMO class: Packing Group: Proper Shipping Name: Transport by air:	9 III Environ	UN:3082 mentally hazardous substance, liquid, n.o.	.S.
IATA: Packing Group: Label: Cargo: Packaging instructions:	9 III 9 914	UN:3082 Maximum quantity: No lin	~
Pass.:	914 914		
Packaging instructions: Special Instructions:	914 A97	Maximum quantity: No lir	11

15. Regulatory information



Contains: EPOXY RESINS (average molecular weight <= 700)

Danger labelling under regulations 67/548/CEE and 1999/45/CE and following amendments and adjustments.

Workers exposed to this chemical agent must undergo health checks according to regulation 98/24/CE.

16. Further information

Text of -R- phrases quoted in section 2 of the sheet.

- R36/38 IRRITATING TO EYES AND SKIN.
- R43 MAY CAUSE SENSITIZATION BY SKIN CONTACT.

R51/53 TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.

GENERAL BIBLIOGRAPHY

- 1. Regulation 1999/45/CE and following amendments;
- 2. Regulation 67/548/CEE and following amendments and adjustments (technical adjustment XXVIII);
- 3. Regulation 91/155/CEE and following amendments;
- 4. The Merck Index. 10th Edition;
- 5. Handling Chemical Safety;
- 6. Niosh Registry of Toxic Effects of Chemical Substances;
- 7. INRS Fiche Toxicologique (toxicological sheet);
- 8. Patty Industrial Hygiene and Toxicology;
- 9. N.I. Sax-Dangerous properties of Industrial Materials-7, 1989 Edition;

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product .

This document must not de regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from imporoper uses.