



PRODUCT

THK 2 Thickening Agent

DESCRIPTION

THK 2 is an organoclay thickening very easily dispersible additive. It can be added at any point in the manufacturing process without requiring the use of a polar activator or the preparation of a pregel.

THK 2 additive gives stable viscosity and controls sag and pigment settling in products such as industrial maintenance coatings, marine paints, anti-corrosive paints, adhesives and sealants.

SPECIFICATION

- | | |
|------------------------------|--|
| - Form: | finely divided powder |
| - Color: | very light cream |
| - Composition : | organic derivative of a montmorillonite clay |
| - Particle size (dispersed): | less than 1 micron |
| - Density: | 1.62 g/cm ³ |
| - Bulk density: | 0.12 g/cm ³ |
| - Packing: | 7 kg units. |

USES

The level of THK 2 additive to be used in a specific system depends on the degree of thickening required. Levels are typically 2 - 6% by weight.

All information and direction contained in this technical data sheet are given in good faith and are based on the best known practical test.

SINIT when having no control over transport, storage, handling, use and application of its product, will disclaim any responsibilities for any unsatisfactory results obtained.

All tests have been carried out at 23 °C

Revised: January 2002.

These data supersede all previously published data.

SINIT S.r.l. – Via V. Chiarugi,76 – 45100 ROVIGO (ITALY)

Tel. ++39. 0425 361961(r.a.) – Fax ++39. 0425 410115

E-MAIL sinit@tin.it www.sinitworks.com

